PB90-166216

Treatment Standards for K069 Nonwastewaters in the Calcium Sulfate Subcategory and Wastewater Forms of K069. Volume 10

(U.S.) Environmental Protection Agency, Washington, DC

8 Nov 89

U.S. Department of Commerce
National Technical Information Service
NTIS

50272-101

REPORT DOCUMENTATION PAGE	1. REPORT NO. EPA/530-SW-90-011J	2.	3. PB90-166216
4. Title and Subtitle MEMORANDUM FROM VERSAR (LAURA FARGO/SCOTT WOLFF) TO MONICA CHATMON-McEADDY (EPA) RE TREATMENT STANDARDS FOR K069 NONWASTEWATERS IN THE CALCIUM SULFATE SUBCATEGORY AND WASTEWATER FORMS OF K069, NOVEMBER 8, 1989			5. Report Date NOVEMBER 1989 6.
7. Author(s) VERSAR			8. Performing Organization Rept. No
9. Performing Organization Name and Address VERSAR 6850 VERSAR CENTER SPRINGFIELD, VA 22151			10. Project/Task/Work Unit No. 11. Contract(C) or Grant(G) No. (C) (G)
12. Sponsoring Organization Name and Address U.S. EPA OFFICE OF SOLID WASTE 401 M STREET, SW WASHINGTON, DC 20460			13. Type of Report & Period Covered MEMORANDUM - 11/89 14.
15. Supplementary Notes			

16. Abstract (Limit: 200 words)

This memorandum presents the technical support and rationale for the development of treatment standards for K069 nonwastewaters in the Calcium Sulfate Subcategory and wastewater forms of K069.

17. Document Analysis a. Descriptors

b. Identifiers/Open-Ended Terms

c. COSATI Field/Group

18. Availability Statement	19. Security Class (This Report)	21. No. of Pages
RELEASE UNLIMITED	UNCLASSIFIED	0
	20. Security Class (This Page) UNCLASSIFIED	22. Price 0

(See ANSI-Z39.18)

REPRODUCED BY
U.S. DEPARTMENT OF COMMERCE
NATIONAL TECHNICAL INFORMATION SERVICE
SPRINGFIELD, VA. 22161

OPTIONAL FORM 272 (4-77)
(Formerly NTIS-35)

EPA/530-SW-90-011J

Versar Inc

MEMORANDUM

TO: Monica Chatmon-McEaddy

cc: J. Strauss
S. Schwartz
5254 File

FROM: Laura Fargo
Scott Wolff

DATE: November 8, 1989

SUBJECT: Treatment Standards for K069 Nonwastewaters in the Calcium Sulfate Subcategory and Wastewater Forms of K069

This memorandum presents the technical support and rationale for the development of treatment standards for K069 nonwastewaters in the Calcium Sulfate Subcategory and wastewater forms of K069.

INTRODUCTION

According to 40 CFR Part 261.32 (hazardous wastes from specific sources), waste code K069 is listed as emission control dust/sludge from secondary lead smelting. In the First Third Final Rule (53 FR 31165, August 17, 1988), EPA established a Calcium Sulfate Subcategory and a Noncalcium Sulfate Subcategory for K069 nonwastewaters. A final BDAT treatment standard of "no land disposal" based on total recycle for those K069 nonwastewaters in the Noncalcium Sulfate Subcategory was promulgated in 53 FR 31165. Treatment standards for K069 nonwastewaters in the Calcium Sulfate Subcategory and wastewater forms of K069 were not promulgated as part of the First Third rulemaking in order to allow the Agency time for additional data collection and analysis.

INDUSTRY AFFECTED

The Calcium Sulfate Subcategory of K069 nonwastewaters was defined by EPA in 53 FR 31165 to cover a single plant (Exide/GBC) which, to EPA's knowledge, is the only plant generating a K069 nonwastewater stream that cannot be directly recycled to recover lead. (Lead recovery is the

treatment standard that was promulgated for the Noncalcium Sulfate Subcategory for nonwastewaters.) This stream is a dewatered venturi scrubber sludge resulting from the lime slurry scrubbing of residual gases from fabric filtration of secondary lead smelter offgases. The resulting wastewater after sludge dewatering is the "derived from" wastewater form of K069. This wastewater can also be generated as leachate from RCRA or CERCLA land disposal activities.

WASTE CHARACTERIZATION

A. **Wastewaters**. The only known characterization data for K069 wastewaters are available in an Office of Water, Effluent Guidelines Division, draft development document (USEPA 1977). These characterization data describe venturi scrubber water generated at the one secondary lead smelting plant that is currently in the EPA-designated Calcium Sulfate Subcategory. Table 1 presents the pertinent data on BDAT list metal constituents from this source.

The Agency believes that K069 wastewater represents a single treatability group based on its expected physical and chemical composition. Specifically, K069 wastewaters are expected to be similar in physical and chemical composition regardless of which subcategory of nonwastewater they are derived from. Hence, K069 wastewaters have not been subcategorized.

B. **Nonwastewaters**. Characterization data submitted by Exide/GBC in response to the First Thirds Proposed rulemaking for K069 waste are summarized in Table 2. These data cover the principal parameters characterizing the Calcium Sulfate Subcategory of K069 nonwastewaters.

APPLICABLE AND DEMONSTRATED TECHNOLOGIES

A. **Wastewaters**. For K069 wastewaters, the Agency believes that the applicable treatment technologies include chemical precipitation

Table 1 Venturi Scrubber Water Characterization Data at the Single Calcium Sulfate Subcategory Plant

Constituent Scrubber water analyses (mg/l)	
Arsenic	1.25
Cadmium	1.62
Lead	54
pH	1.5

Source: USEPA 1977.

Versar INC.

Table 2 Summarized Characterization Data for the Calcium Sulfate Subcategory of K069 Nonwastewaters

Parameter	Value or range	Comments
Percent solids	20-61	Typically around 40
pH (solids in water)	6-12	
Heating value	N/A	
Ignitability	N/A	Waste is not ignitable
Metals content (wet basis), ppm		
Arsenic	494	
Barium	56	
Cadmium	13-130	
Total chromium	10	
Lead	650-3327	Too low to recycle to lead smelter for recovery of lead
Mercury	515	
Nickel	8	
Selenium	23-130	
Silver	3	
Copper	22	
Molybdenum	2	
Zinc	16	
Sulfate/sulfite content, %	31	
TCLP leachate, mg/l		
Cadmium	0.21-1.47	
Lead	0.66-0.72	
EP leachate, mg/l		
Arsenic	<0.1-3.08	
Barium	<0.1-2.9	
Cadmium	0.1-13.7	
Total chromium	0.007-0.27	
Lead	0.085-24.3	
Mercury	<0.02-0.11	
Selenium	0.002-0.36	
Silver	0.01-0.07	
Oil and grease, %	<0.02	
Organics, ppm	<1	

Source: Morgan, Lewis, and Backius 1988.

followed by settling and/or filtration. The Agency has identified these treatment technologies because they are designed to reduce the concentration of metals in wastewaters. In addition, the treatment system consisting of chemical precipitation followed by settling and/or filtration is an applicable technology for removal of both dissolved and suspended metals from K069 wastewaters. Other applicable technologies include ion exchange and physical treatment methods that remove suspended solids from wastewaters (such as clarification and flocculation).

B. **Nonwastewaters**. Applicable treatment for the Calcium Sulfate Subcategory of K069 nonwastewater is stabilization to reduce the leachability of BDAT list metals. All of the applicable wastewater and nonwastewater treatment technologies are demonstrated because they are used on a full-scale commercial basis for treatment of metal bearing wastes. Metals precipitation, followed by settling, filtering, and dewatering of solids, and stabilization are widely practiced metals treatment technologies.

Additional information on technologies identified as applicable for K069 wastes can be found in the Treatment Technology Background Document (USEPA 1989).

PERFORMANCE DATA BASE

This section discusses all available performance data associated with K069 nonwastewaters in the Calcium Sulfate Subcategory and wastewater forms of K069.

A. **Wastewaters**. The only treatability data relative to K069 wastewaters are from the Exide/GBC lead smelting plant. At this facility, K069 wastewater is sent to an onsite industrial wastewater treatment plant where it is lime-treated, clarified, and filtered in combination with other plant wastewaters. The treatability data for the combined wastewaters including waste code K069, have appeared in the previously

Table 3 EPA-Collected Data on Alkaline Treatment (Chemical Precipitation) of Secondary Lead Smelter Wastewaters

Constituent	Influent concentration (mg/l)	Effluent concentration (mg/l)
Pb	76	0.41
As	0.024	0.03
Cd	0.83	0.005
pH	1.3	8.85

Source: USEPA 1977, Table VII-15, p. 187. Analyses are on composite samples of influent and effluent.

Table 4 Monthly Plant-Collected Effluent Data Following Alkaline Treatment (Chemical Precipitation) on BDAT Constituents

Year 1975	Selected Constituent Effluent Level (mg/l)				
	pH	Pb		As	
Month	Average	Average	Maximum	Average	Maximum
January	7.72	0.39	2.24	<0.004	0.037
February	7.33	0.37	1.63	<0.004	0.015
March	7.57	0.57	1.43	<0.009	0.033
April	8.14	0.35	0.88	<0.007	0.027
May	7.54	0.36	2.30	<0.004	0.026
June	8.03	0.104	0.32	0.003	0.008
July	-	-	-	-	-
August	8.31	<0.072	0.17	<0.002	0.002
September	7.94	0.16	0.74	0.003	0.019
October	7.93	0.228	2.65	0.003	0.007
November	8.12	0.155	0.81	0.004	0.027
December	-	-	-	-	-

Source: USEPA 1988.

referred to ELG document and are presented in Table 3. Additional plant data (from the same ELG document) based on alkaline treatment (chemical precipitation) for lead and arsenic are shown in Table 4.

In addition, the Agency has 11 data sets for treatment of metal-bearing wastewaters by hexavalent chromium reduction, chemical precipitation, and dewatering of the precipitate. These data are presented in Tables 5 through 15. The metal bearing wastewaters included waste code K062, and these data were previously used in the development of treatment standards for K062 in the First Third Final Rule (USEPA 1988b). The Agency believes that these K062 data can be used to assess the performance of these technologies for K069 wastewaters, since the untreated K062 wastewaters contain much higher metals concentrations than K069 wastewaters are expected to contain.

B. Nonwastewaters. Treatment performance data for the Calcium Sulfate Subcategory of K069 nonwastewaters specifically are not available. However, performance data are available from stabilization tests on F006 and K061 nonwastewaters, which are believed to be similar to K069 nonwastewater in the Calcium Sulfate Subcategory. The data presented in Table 16 represent performance data developed from stabilization of F006 waste, while the data in Table 17 represent treatment of K061 wastes. These data were previously used in the development of treatment standards for F006 and K061 in the First Third Final Rule (USEPA a,c).

Table 5 Treatment Performance Data for K062 - EPA-Collected Data

Sample Set #1

Constituent	Untreated K062 waste (mg/l) Sample No. 801	Untreated K062 waste (mg/l) Sample No. 802	Untreated waste composite[a] (mg/l) Sample No. 805	Treated waste (wastewater) (mg/l) Sample No. 806
Arsenic	3	<1	<1	<0.1
Cadmium	<5	<5	13	<0.5
Chromium (hexavalent)	I	I	893	0.011
Chromium (total)	1800	7000	2581	0.12
Copper	865	306	138	0.21
Lead	<10	<10	64	<0.01
Nickel	3200	2600	471	0.33
Zinc	<2	<2	116	0.125

Design and Operating Data

	Design value	Operating value
pH	8-10	9

I = Color interference.

[a]The untreated waste composite is a mixture of the untreated K062 waste streams shown on this table, along with other non-K062 waste streams.

Source: USEPA 1988b.

Versar INC. Table 6 Treatment Performance Data for K062 - EPA-Collected Data

Sample Set #2

Constituent	Untreated K062 waste (mg/l) Sample No. 801	Untreated K062 waste (mg/l) Sample No. 802	Untreated waste composite[a] (mg/l) Sample No. 813	Treated waste (wastewater) (mg/l) Sample No. 814
Arsenic	3	<1	<1	<0.1
Cadmium	<5	<5	10	<0.5
Chromium (hexavalent)	I	I	807	0.12
Chromium (total)	1800	7000	2279	0.19
Copper	865	306	133	0.15
Lead	<10	<10	54	<0.01
Nickel	3200	2600	470	0.33
Zinc	<2	<2	4	0.115

Design and Operating Data

	Design value	Operating value
pH	8-10	9

I = Color interference.

[a]The untreated waste composite is a mixture of the untreated K062 waste streams shown on this table, along with other non-K062 waste streams.

Source: USEPA 1988b.

Versar INC.

Table 7 Treatment Performance Data for K062 - EPA-Collected Data

Sample Set #3

Constituent	Untreated K062 waste (mg/l) Sample No. 817	Untreated K062 waste (mg/l) Sample No. 802	Untreated waste composite[a] (mg/l) Sample No. 821	Treated waste (wastewater) (mg/l) Sample No. 822
Arsenic	3	<1	<1	<0.1
Cadmium	<5	<5	5	<0.5
Chromium (hexavalent)	I	I	775	I
Chromium (total)	1700	7000	1990	0.20
Copper	425	306	133	0.21
Lead	<10	<10	<10	<0.01
Nickel	100310	2600	16330	0.33
Zinc	7	<2	3.9	0.140

Design and Operating Data

	Design value	Operating value
pH	8-10	10

I = Color interference.

[a]The untreated waste composite is a mixture of the untreated K062 waste streams shown on this table, along with other non-K062 waste streams.

Source: USEPA 1988b.

Table 8 Treatment Performance Data for K062 - EPA-Collected Data

Sample Set #4

Constituent	Untreated K062 waste (mg/l) Sample No. 827	Untreated K062 waste (mg/l) Sample No. 802	Untreated K062 waste (mg/l) Sample No. 817	Untreated waste composite[a] (mg/l) Sample No. 829	Treated waste (wastewater) (mg/l) Sample No. 830
Arsenic	2	<1	3	<1	<1
Cadmium	<5	<5	5	<5	<0.5
Chromium (hexavalent)	1	I	1	0.6	0.042
Chromium (total)	142	7000	1700	556	0.10
Copper	42	306	425	88	0.07
Lead	<10	<10	<10	<10	<0.01
Nickel	650	2600	41000	6610	0.33
Zinc	3	<2	7	84	1.62

Design and Operating Data

	Design value	Operating value
pH	8-10	9

I = Color interference.

[a]The untreated waste composite is a mixture of the untreated K062 waste streams shown on this table, along with other non-K062 waste streams.

Source: USEPA 1988b.

Versar INC

Table 9 Treatment Performance Data for K062 - EPA-Collected Data

Sample Set #5

Constituent	Untreated K062 waste (mg/l) Sample No. 801	Untreated K062 waste (mg/l) Sample No. 802	Untreated K062 waste (mg/l) Sample No. 817	Untreated waste composite[a] (mg/l) Sample No. 837	Treated waste (wastewater) (mg/l) Sample No. 838
Arsenic	3	<1	3	<1	<0.1
Cadmium	<5	<5	5	<5	<0.5
Chromium (hexavalent)	I	I	I	917	0.058
Chromium (total)	1800	7000	1700	2236	0.11
Copper	865	306	425	91	0.14
Lead	<10	<10	<10	18	0.01
Nickel	3200	2600	41000	1414	0.31
Zinc	<2	<2	7	71	0.125

Design and Operating Data

	Design value	Operating value
pH	8-10	8

I = Color interference.

[a]The untreated waste composite is a mixture of the untreated K062 waste streams shown on this table, along with other non-K062 waste streams.

Source: USEPA 1988b.

Versar INC. Table 10 Treatment Performance Data for K062 - EPA-Collected Data

Sample Set #6

Constituent	Untreated K062 waste (mg/l) Sample No. 801	Untreated K062 waste (mg/l) Sample No. 802	Untreated waste composite[a] (mg/l) Sample No. 845	Treated waste (wastewater) (mg/l) Sample No. 846
Arsenic	3	<1	<1	<0.1
Cadmium	<5	<5	<5	<0.5
Chromium (hexavalent)	I	I	734	I
Chromium (total)	1800	7000	2548	0.10
Copper	865	306	149	0.12
Lead	<10	<10	<10	<0.01
Nickel	3200	2600	588	0.33
Zinc	<2	<2	4	0.095

Design and Operating Data

	Design value	Operating value
pH	8-10	8

I = Color interference.

[a]The untreated waste composite is a mixture of the untreated K062 waste streams shown on this table, along with other non-K062 waste streams.

Source: USEPA 1988b.

Versar INC. Table 11 Treatment Performance Data for K062 - EPA-Collected Data

Sample Set #7

Constituent	Untreated K062 waste (mg/l) Sample No. 801	Untreated K062 waste (mg/l) Sample No. 802	Untreated waste composite[a] (mg/l) Sample No. 853	Treated waste (wastewater) (mg/l) Sample No. 854
Arsenic	3	<1	<1	<0.1
Cadmium	<5	<5	10	<0.5
Chromium (hexavalent)	I	I	769	0.12
Chromium (total)	1800	7000	2314	0.12
Copper	865	306	72	0.16
Lead	<10	<10	108	<0.01
Nickel	3200	2600	426	0.40
Zinc	<2	<2	171	0.115

Design and Operating Data

	Design value	Operating value
pH	8-10	9

I = Color interference.

[a]The untreated waste composite is a mixture of the untreated K062 waste streams shown on this table, along with other non-K062 waste streams.

Source: USEPA 1988b.

Table 12 Treatment Performance Data for K062 - EPA-Collected Data

Sample Set #8

Constituent	Untreated K062 waste (mg/l) Sample No. 859	Untreated K062 waste (mg/l) Sample No. 801	Untreated waste composite[a] (mg/l) Sample No. 861	Treated waste (wastewater) (mg/l) Sample No. 862
Arsenic	<1	3	<1	<0.1
Cadmium	<5	<5	<5	<0.5
Chromium (hexavalent)	0.220	I	0.13	<0.01
Chromium (total)	15	1800	831	0.15
Copper	151	865	217	0.16
Lead	<10	<10	212	<0.01
Nickel	90	3200	669	0.36
Zinc	7	9	151	0.13

Design and Operating Data

	Design value	Operating value
pH	8-10	9

I = Color interference.

[a]The untreated waste composite is a mixture of the untreated K062 waste streams shown on this table, along with other non-K062 waste streams.

Source: USEPA 1988b.

Table 13 Treatment Performance Data for K062 - EPA-Collected Data

Sample Set #9

Constituent	Untreated K062 waste (mg/l) Sample No. 867	Untreated K062 waste (mg/l) Sample No. 801	Untreated K062 waste (mg/l) Sample No. 802	Untreated waste composite[a] (mg/l) Sample No. 869	Treated waste (wastewater) (mg/l) Sample No. 870
Arsenic	<0.1	3	<1	<1	<0.1
Cadmium	<0.5	<5	<5	<5	<0.5
Chromium (hexavalent)	0.079	I	I	0.07	0.041
Chromium (total)	6	1800	7000	939	0.10
Copper	5	865	306	225	0.08
Lead	<1	<10	<10	<10	<0.01
Nickel	4	3200	2600	940	0.33
Zinc	0.4	<2	<2	5	0.06

Design and Operating Data

	Design value	Operating value
pH	8-10	10

I = Color interference.

[a]The untreated waste composite is a mixture of the untreated K062 waste streams shown on this table,
along with other non-K062 waste streams.

Source: USEPA 1988b.

Versar INC. Table 14 Treatment Performance Data for K062 - EPA-Collected Data

Sample Set #10

Constituent	Untreated K062 waste (mg/l) Sample No. 801	Untreated waste composite[a] (mg/l) Sample No. 885	Treated waste (wastewater) (mg/l) Sample No. 862
Arsenic	<3	<1	<0.10
Cadmium	<5	<5	<0.5
Chromium (hexavalent)	I	0.08	0.106
Chromium (total)	1800	395	0.12
Copper	865	191	0.14
Lead	<10	<10	<0.01
Nickel	3200	712	0.33
Zinc	<2	5	0.070

Design and Operating Data

	Design value	Operating value
pH	8-10	9

I = Color interference.

[a]The untreated waste composite is a mixture of the untreated K062 waste streams shown on this table, along with other non-K062 waste streams.

Source: USEPA 1988b.

Versar INC. Table 15 Treatment Performance Data for K062 - EPA-Collected Data

Sample Set #11

Constituent	Untreated K062 waste (mg/l) Sample No. 801	Untreated K062 waste (mg/l) Sample No. 859	Untreated waste composite[a] (mg/l) Sample No. 893	Treated waste (wastewater) (mg/l) Sample No. 894
Arsenic	3	<1	<1	<0.10
Cadmium	<5	<5	23	<5
Chromium (hexavalent)	I	0.220	0.30	<0.01
Chromium (total)	1800	15	617	0.18
Copper	865	151	137	0.24
Lead	<10	<10	136	<0.01
Nickel	3200	90	382	0.39
Zinc	<2	7	135	0.100

Design and Operating Data

	Design value	Operating value
pH	8-10	9

I = Color interference.

[a]The untreated waste composite is a mixture of the untreated K062 waste streams shown on this table, along with other non-K062 waste streams.

Source: USEPA 1988b.

Table 16 Treatment Performance Data for Stabilization of F006 Nonwastewater[a]

Source	Mix ratio[b]	Metal concentrations (ppm)							
		Barium	Cadmium	Chromium	Copper	Lead	Nickel	Silver	Zinc
Unknown									
Unstabilized									
As received	-	-	-	-	-	-	435	-	1560
TCLP	-	-	-	-	-	-	0.71	-	0.16
Stabilized									
TCLP	0.2	-	-	-	-	-	0.05	-	0.03
Auto part manufacturing									
Unstabilized									
As received	-	-	31.3	755	7030	409	989	6.62	4020
TCLP	-	-	2.21	0.76	638	10.7	22.7	0.14	219
Stabilized									
TCLP	0.5	-	0.01	0.45	0.27	0.39	0.03	0.06	0.01
Aircraft overhauling									
Unstabilized									
As received	-	85.5	67.3	716	-	-	259	-	631
TCLP	-	1.41	1.13	0.43	-	-	1.1	-	5.41
Stabilized									
TCLP	0.2	0.34	0.06	0.09	-	-	0.27	-	0.03
Zinc plating									
Unstabilized									
As received	-	17.2	1.30	-	1510	-	37	9.05	90,200
TCLP	-	0.84	0.22	-	4.6	-	0.52	0.16	2050
Stabilized									
TCLP	0.5	0.25	0.01	-	0.21	-	0.02	0.05	0.04
Unknown									
Unstabilized									
As received	-	14.3	720	12,200	160	-	701	-	25,900
TCLP	-	0.38	23.6	25.3	1.14	-	9.78	-	867
Stabilized									
TCLP	0.5	0.21	0.01	0.44	0.31	-	0.04	-	0.03

Table 16 (continued)

Source	Mix ratio[a]	Metal concentrations (ppm)							
		Barium	Cadmium	Chromium	Copper	Lead	Nickel	Silver	Zinc
Small engine manufacturing									
Unstabilized									
As received	-	-	7.28	3100	1220	113	19,400	4.08	27,800
TCLP	-	-	0.3	38.7	31.7	3.37	730	0.12	1200
Stabilized									
TCLP	0.5	-	0.01	0.89	0.31	0.39	0.06	0.06	0.040
Circuit board manufacturing									
Unstabilized									
As received	-	-	5.39	42,900	10,600	156	13,000	-	120
TCLP	-	-	0.60	360	8.69	1.0	152	-	0.62
Stabilized									
TCLP	0.5	-	0.01	1.41	0.45	0.41	0.11	-	0.020
Unknown									
Unstabilized									
As received	-	15.3	5.81	-	17,600	169	23,700	8.11	15,700
TCLP	-	0.53	0.18	-	483	4.22	644	0.31	650
Stabilized									
TCLP	0.5	0.294	0.01	-	0.35	0.40	0.04	0.06	0.020
Unknown									
Unstabilized									
As received	-	19.2	-	-	27,400	24,500	5,730	-	322
TCLP	-	0.28	-	-	16.9	50.2	16.1	-	1.29
Stabilized									
TCLP	0.5	0.087	-	-	0.50	0.29	<0.02	-	<0.01

[a]Adjusted analytical results (referred to as accuracy-corrected concentrations) used for comparing the performance of one technology to that of another and for calculating treatment standards for those constituents to be regulated.

[b] Mix ratio = $\frac{\text{weight of reagent}}{\text{weight of waste}}$

Source: USEPA 1988a.

Table 17 Summary of Treatment Performance Data for Stabilization of K061 Nonwastewater Using a Lime/Flyash Binder (EPA Collected Data)

Constituents	Untreated waste Total (ppm)	Untreated waste TCLP (mg/l)	Treated waste TCLP (mg/l)
Antimony	294	0.040	<0.050
Arsenic	36	<0.010	<0.010
Barium	238	0.733	0.431 - 0.500
Beryllium	0.15	<0.001	<0.001
Cadmium	481	12.8	0.033 - 0.073
Chromium	1,370	<0.007	0.053 - 0.093
Copper	2,240	0.066	<0.004 - 0.015
Lead	20,300	45.1	0.066 - 0.150
Mercury	3.8	0.0026	0.0016 - 0.0018
Nickel	243	0.027	<0.012
Selenium	<5.0	<0.050	<0.025
Silver	59	0.021	<0.003
Thallium	<1.0	0.038	0.011 - 0.014
Vanadium	25	<0.006	0.080 - 0.089
Zinc	244,000	445	0.179 - 0.592
Oil and grease	282		
Sulfates	8,440		
Chlorides	19,300		
TOC	4,430		

Source: USEPA 1988c.

IDENTIFICATION OF BEST DEMONSTRATED AVAILABLE TECHNOLOGY (BDAT)

This section presents the rationale for the determination of best demonstrated available technology (BDAT) for K069 nonwastewaters in the Calcium Sulfate Subcategory and wastewater forms of K069. The Agency examined all the available treatment performance data for the demonstrated technologies to determine which is best. For K069 wastewaters, the Agency has treatment performance data for one facility that treats K069 wastewaters using chemical precipitation. In addition, treatment performance data are available for metal-bearing wastewaters containing K062 waste, which is similar to K069 wastewaters. Treatment performance data are not available for the Calcium Sulfate Subcategory of K069 nonwastewaters specifically. However, performance data are available from stabilization tests on F006 and K061 nonwastewaters.

A. Wastewater. As stated previously, the Agency has one data set for treatment of K069 wastewaters using a chemical precipitation process. These data (see Table 3) are not usable by the BDAT program to assess the performance of the chemical precipitation system because no analytical QA/QC is available. Additionally, the data represent wastewater generated from nonwastewater with low lead concentrations (i.e., K069 nonwastewater in the Calcium Sulfate Subcategory). Hence, it is believed that K069 wastewater with higher lead concentrations may be generated.

Based on a comparison of metals concentrations in the untreated wastes, the Agency has determined that the K062 wastewaters are more difficult to treat than K069 wastewaters, and consequently believes that the treatment performance can be achieved for all forms of K069 wastewaters. Available treatment performance data presented in Tables 5 through 15 for treatment of K062 wastewaters by chromium reduction, chemical precipitation, and filtration show that this treatment is effective. Hexavalent chromium reduced from 893 mg/l to 0.011 mg/l;

total chromium reduced from 2,581 mg/l to 0.12 mg/l; copper from 138 mg/l to 0.2; cadmium from 13 mg/l to <0.5 mg/l; nickel from 471 mg/l to 0.33; lead from 64 mg/l to <0.01 mg/l; and zinc from 116 mg/l to 0.125 mg/l. These data collected from this treatment train for K062 wastewaters were obtained from a well-designed and well-operated system and therefore can be used to compare treatment performance of demonstrated technologies.

Based on the evaluation of the available treatment performance data and other information, the Agency believes that the treatment train consisting of hexavalent chromium reduction, chemical precipitation and settling, and/or filtration represents BDAT for K069 wastewaters.

B. Nonwastewaters. EPA compared the F006 and K061 wastes to determine which would be more representative of K069 nonwastewaters in the Calcium Sulfate Subcategory. Included in this analysis were waste parameters that affect the stabilization treatment such as concentrations of metals, sulfide levels, and waste generation information. In general, both K061 nonwastewaters and F006 nonwastewaters contain similar metal constituents in higher concentrations than do K069 nonwastewaters. The sulfate levels in both K061 and F006 are insignificant compared to the high sulfate level in K069. The generating process by which the K061 nonwastewater sludge is generated more closely resembles the process that generates the K069 nonwastewater (both are emission control dust sludges). Based on this analysis, EPA considers the K061 nonwastewaters more representative than F006 nonwastewaters of K069 nonwastewaters in the Calcium Sulfate Category.

The data on generation of the K069 wastes in the Calcium Sulfate Subcategory indicate that during the generation of this waste, excess lime is added to the K069 as it is being generated. This excess lime is expected to act as a stabilizing agent, with the resulting waste exhibiting a lower leachability than would be expected from a waste that was generated without the addition of excess lime. Conversely, characterization data of this waste indicate a high level of sulfates in

the waste, which affects treatment performance of some solidification processes. Regardless of the high level of sulfates, the Agency believes that substantial treatment levels may be achievable simply by the current practice of addition of excess lime during generation. Therefore, EPA believes that the data on stabilization of K061 can be used to establish treatment performance standards for K069 nonwastewaters in the Calcium Sulfate Subcategory.

Available treatment performance data presented in Table 17 for stabilization of K061 nonwastewater using a lime/flyash binder show that this treatment is effective. Stabilization technology adopted as BDAT for the Low Zinc Subcategory of K061 nonwastewater was able to produce TCLP leachate levels of 0.066 to 0.150 mg/l lead and 0.033 to 0.073 mg/l cadmium from a K061 nonwastewater containing 20,300 ppm lead and 481 ppm cadmium. Based on this analysis and other data and information explained in the K061 Background Document (USEPA 1988a), the Agency maintains that stabilization using a lime/flyash binder represents BDAT for K069 nonwastewaters in the Calcium Sulfate Subcategory.

Selection of Regulated Constituents

A. Wastewaters. The BDAT list metals found in treatable concentrations in the untreated K069 wastewater (see Table 1) are lead and cadmium. Arsenic was also present in low concentrations and is expected to be treated and controlled along with the lead and cadmium. Based on these findings, the regulated constituents are lead and cadmium.

B. Nonwastewaters. Leachate data for K069 nonwastewaters in the Calcium Sulfate Subcategory (see Table 2) show that lead and cadmium are present at treatable concentrations, while other metal constituents are present at lower concentrations. The Agency does not expect the presence of other BDAT metals at treatable levels. Furthermore, other BDAT list metal constituents that are not regulated are expected to be treated by a well-designed and well-operated treatment system. Based on these findings, the regulated constituents are lead and cadmium.

Development of Treatment Standards

This section presents the treatment standards for the regulated constituents described previously. A description of the rationale and procedures for calculating treatment standards is presented in the K062 wastewater background document (1988b) and K061 nonwastewater background document (1988a). The BDAT treatment standards presented in this section (1) are reflective of treatment performance data from a well-designed and well-operated treatment system, (2) account for analytical limitations, and (3) have been adjusted for variability caused by treatment, sampling, and analytical techniques and procedures.

A. Wastewaters. EPA compared the K062 wastewaters and K069 waste stream shown in Table 1 with regard to concentrations of metals. In general, both K069 wastewaters and K062 wastewaters contain similar metal constituents but K062 has BDAT list metals at higher concentrations than do K069 wastewaters. EPA would expect that the K062 wastewaters would be more difficult to treat effectively by the treatment system consisting of chemical precipitation, settling, and/or filtration.

Based on the available data relative to waste characteristics, the Agency has no reason to believe that the treatment levels achieved for K062 wastewaters cannot be achieved for K069 wastewaters. Accordingly, EPA is using these performance data for hexavalent chromium reduction, chemical precipitation, and settling and/or filtration to establish treatment standards for K069 wastewaters. Therefore, the Agency is transferring the treatment performance data from this treatment train for K062 wastewaters to K069 wastewaters.

The 11 data sets for treatment of K062 wastewaters by hexavalent chromium reduction, chemical precipitation, and dewatering of the

precipitate were determined to represent treatment by a well-designed and well-operated treatment system (USEPA 1988b). One data set for cadmium was deleted (Sample Set #11) because of an artificially high detection limit of 5 ppm, which deviated from the other 10 data points, which had detection limits of 0.5.

Table 18 presents the specific BDAT treatment standards for K069 wastewater. For the BDAT list metal constituents, treatment standards in the wastewater reflect the total constituent concentration. The units for the total constituent concentration are mg/l (parts per million on a weight-by-volume basis) for the wastewater. If the concentrations of the regulated constituents in the K069, as generated, are lower than or equal to those of the BDAT treatment standards, then treatment is not necessary as a prerequisite to land disposal.

Table 18 BDAT Treatment Standards for K069 Wastewaters

Constituent	Maximum for any single grab sample Wastewater Total concentration mg/l
Cadmium	1.61
Lead	0.04

B. **Nonwastewaters**. Specifically, EPA believes that the data on stabilization of K061 waste can be used to assess treatment performance for cadmium and lead in K069 nonwastewaters.

Since the process by which the K069 nonwastewater sludge is generated closely resembles the process that generates the K061 nonwastewater (both

are emission control dust/sludges), the Agency has no reason to believe that the treatment levels achieved for cadmium and lead in K061 cannot also be achieved for K069. Accordingly, EPA is using K061 performance data to establish treatment standards for cadmium and lead in the Calcium Sulfate Subcategory of K069 nonwastewaters.

The data presented for stabilization of K061 nonwastewaters (see Table 17) have been evaluated by EPA to ensure that any data representing poor design and poor operation were deleted and that all data were adjusted for analytical accuracy. As a result, the data for K061 stabilization were determined to represent treatment by a well-designed and well-operated treatment system.

Table 19 presents the specific BDAT treatment standards for K069 nonwastewater. For the BDAT list metal constituents, treatment standards in nonwastewater reflect the concentration of constituents in the leachate from the Toxicity Characteristic Leaching Procedure (TCLP). The units for the leachate concentration are mg/l (parts per million on a weight-by-volume basis). If the concentrations of the regulated constituents in the K069, as determined in the leachate analytical process, are lower than or equal to the BDAT treatment standards, then treatment is not necessary as a prerequisite to land disposal.

Table 19 BDAT Treatment Standards for K069 Nonwastewaters In The Calcium Sulfate Subcategory

	Maximum for any single grab sample
	Nonwastewater
	TCLP leachate concentration
Constituent	mg/l
Cadmium	0.14
Lead	0.24

References

Morgan, Lewis, and Backius. 1988. Philadelphia, PA. Letter to U.S. Environmental Protection Agency, Washington, D.C., May 20, 1988, to Docket Regarding EPA's Proposed Land Disposal Restrictions for First Third of Scheduled Wastes, Docket No. LDR7000007.

USEPA. 1977. Draft. Development Document for Effluent Limitations Guidelines and New Source Performance Standards for the Miscellaneous Nonferrous Metals Segment of the Nonferrous Metals Manufacturing Point Source Category. U.S. Environmental Protection Agency. 440/1-76/067.

USEPA. 1988a. Final Best Demonstrated Available Technology (BDAT) Background Document for F006. August 1988. Washington, D.C.: U.S. Environmental Protection Agency. EPA/530-SW-88-031L.

USEPA. 1988b. Final Best Demonstrated Available Technology (BDAT) Background Document for K062. August 1988. Washington, D.C., U.S. Environmental Protection Agency. EPA/530-SW-88-031E.

USEPA. 1988c. Final Best Demonstrated Available Technology (BDAT) Background Document for K061. August 1988. Washington, D.C., U.S. Environmental Protection Agency. EPA/530-SW-88-031D.

USEPA. 1989. U.S. Environmental Protection Agency, Office of Solid Waste. Treatement Technology Background Document. Washington, D.C.: U.S. Environmental Protection Agency.